



AIR COMPRESSORS

Fast Stats



GR100



GR152CM



GR254CTS



GR2540LR



GR309EDV



GR55G10X



GR90G10X

Peak Horsepower	1.0 HP	2.0 HP	2.5 HP	2.5 HP	3.0 HP	5.5 HP	9.0 HP
Tank Capacity	1.0 gal.	2.0 gal.	4.3 gal.	4.0 gal.	9.0 gal.	10.0 gal.	10.0 gal.
Lubrication	Oil-free	Oil-free	Oil	Oil	Oil	Oil	Oil
Draw	5 amps	8 amps	14.2 amps	12 amps	115 volts: 15 amps 230 volts: 7.5 amps	N/A	N/A
Decibels	69	75	79	76	79	77	79
PSI On/Off	95 / 125	95 / 125	95 / 125	110 / 150	95 / 125	95 / 125	95 / 125
CFM	0.6 at 90 PSI	2.6 at 90 PSI	4.0 at 100 PSI	4.2 at 90 PSI	7.0 at 90 PSI	12.5 at 100 PSI	18.5 at 100 PSI
Pump-Up	50 seconds	50 seconds	74 seconds	76 seconds	83 seconds	59 seconds	41 seconds
Recovery	34 seconds	10 seconds	23 seconds	18 seconds	19 seconds	15 seconds	10 seconds
RPM	3450	3450	3450	1725	1060	1210	1250
Height	13.4 in.	14.9 in.	17.0 in.	20.0 in.	23.0 in.	25.0 in.	28.0 in.
Length	14.6 in.	18.9 in.	20.0 in.	23.6 in.	45.0 in.	47.0 in.	49.0 in.
Width	14.2 in.	14.9 in.	15.0 in.	22.0 in.	19.0 in.	19.0 in.	19.0 in.
Weight	23 lb.	37 lb.	56 lb.	90 lb.	162 lb.	198 lb.	220 lb.
Motor Type	Induction	Induction	Induction	Induction	Induction	Honda® Gas Engine	Honda® Gas Engine
Life Expectancy	4,000 hours	4,000 hours	10,000 hours	10,000 hours	10,000 hours	10,000 hours	10,000 hours

1-Year Warranty on All Compressors



AIR COMPRESSORS

Fast Stats



GR100



GR152CM



GR254CTS



GR2540LR



GR309EDV



GR55G10X



GR90G10X

	GR100	GR152CM	GR254CTS	GR2540LR	GR309EDV	GR55G10X	GR90G10X
Finish Tool Capacity*	1 x	3 x	5 x	5 x	7 x	6 x	8 x
Stapler Capacity*	1 x	2 x	3 x	3 x	4 x	5 x	7 x
Roofing Nailer Capacity*	0	1 x	2 x	2 x	3 x	5 x	7 x
Framing Nailer Capacity*	0	1 x	2 x	2 x	3 x	5 x	7 x

*Tool capacity can vary due to rate of actuation

1-Year Warranty on All Compressors

PRIME SOURCE
BUILDING PRODUCTS, INC.

© 2013 PrimeSource Building Products, Inc.

800-676-7777

www.grip-rite.com

www.primesourcebp.com

Grip-Rite® compressors are distributed by PrimeSource Building Products, Inc.